












# Radial Open and Shielded Bearings

BORE d		O.D. D		WIDTH B		BASIC NUMBER	REFERENCE DIAMETER (MM)		FILLET RADIUS r		LOAD RATINGS N	
MM	INCH	MM	INCH	MM	INCH		L <sub>o</sub>	L <sub>i</sub>	MM	INCH	DYN. C <sub>r</sub>	STATIC C <sub>or</sub>
5	.1969	19	.7480	6	.2362	635	16.68	9.20	0.3	.012	2614	1053
6	.2362	19	.7480	6	.2362	626	16.68	9.20	0.3	.012	2614	1053
7	.2756	19	.7480	6	.2362	607	16.68	9.20	0.3	.012	2614	1053
7	.2756	22	.8661	7	.2756	627	19.10	10.80	0.3	.012	3297	1368
8	.3150	22	.8661	7	.2756	608	19.10	10.80	0.3	.012	3297	1368
9	.3543	24	0.9449	7	.2756	*609	19.10	12.40	0.3	.012	3297	1368
9	.3543	26	1.0236	8	.3150	*629	22.80	12.88	0.3	.012	4578	1970
10	.3937	26	1.0236	8	.3150	*6000	22.80	13.75	0.3	.012	4578	1970

\* Note: Limited Availability




OPEN BEARING

OPEN BEARING



METAL SHIELD



EXTERNAL  
RETAINING RING  
NR TYPE

NOTES:

1. Dimensions in millimeters unless otherwise noted.
2. All bearings in this series are made of chrome alloy steel.
3. r = Maximum shaft or housing fillet radius that bearing corners will clear.