


Pos.11: DIN912 M10x35
 Pos.9: O-Ring: 565x3
 Pos.8: O-Ring: 522x14
 Pos.7: Schraube / screw DIN 908: M10x1
 Pos.6: Scheibe / disc DIN 7603: A10x13.5
 Schraubenanzugsmoment (Pos.3) $T_A = 1000\text{Nm}$ Drehmoment / torque $T_{KN} = 500000\text{ Nm}$
 screw tightening torque (Pos.3) $T_A = 1000\text{Nm}$ $T_{Kmax.} = 1000000\text{ Nm}$
ACHTUNG / ATTENTION
 Schrauben bei Auslieferung handfest angezogen.
 Screws are not tightened at delivery.

| | | | | | |
|--|-----------------------|--|-----|----------------------------|-----------------|
| Oberflächenguete nach DIN ISO 1302 Reihe 2 Surface quality acc. to DIN ISO 1302 line 2 | | Schutzvermerk ISO 16016 beachten Note protection mark acc. to ISO 16016 | | | |
| Allgemeintoleranzen nach DIN ISO 2768 - mH General tolerances acc. to DIN ISO 2768 - mH | | Masstab Scale | 1:5 | Format DIN Size | A3 |
| GEARex 100 Ø390 Ø390 Bauart DAB | |  KTR-Kupplungstechnik GmbH D-48407 Rheine | | | |
| gezeichnet drawn | Werkstoff Material | Teilnummer Part number | Kz | Lfd.-Nr. Current number | Index Change |
| Datum 30.08.11 | DIN | | M | 543145 | 0 |
| Name SCHP | Gewicht Weight | 697.742 | | | |

Für Montage, Betrieb & Wartung, Betriebs-/ Montageanleitung KTR-N 40310 beachten.
 For assembly, operation & maintenance, observe operating-/ assembly instructions KTR-N 40310.