


Pos.11: DIN912 M10x35
 Pos.9: O-Ring: 515x3
 Pos.8: O-Ring: 474x14
 Pos.7: Schraube / screw DIN 908: M10x1
 Pos.6: Scheibe / disc DIN 7603: A10x13.5
 Schraubenanzugsmoment (Pos.3) $T_A = 1000\text{Nm}$
 Drehmoment / torque $T_{KN} = 380000\text{ Nm}$
 screw tightening torque (Pos.3) $T_A = 1000\text{Nm}$
 $T_{Kmax.} = 760000\text{ Nm}$
ACHTUNG / ATTENTION
 Schrauben bei Auslieferung handfest angezogen.
 Screws are not tightened at delivery.

| | | | |
|--|-----------------------|--|----------------------------|
| Oberflächenguete nach DIN ISO 1302 Reihe 2 Surface quality acc. to DIN ISO 1302 line 2 | | Schutzvermerk ISO 16016 beachten Note protection mark acc. to ISO 16016 | |
| Allgemeintoleranzen nach DIN ISO 2768 - mH General tolerances acc. to DIN ISO 2768 - mH | | Masstab Scale | 11:50 |
| | | Format DIN Size | A3 |
| GEARex 90 Ø180 Ø180 Bauart DB | |  KTR-Kupplungstechnik GmbH D-48407 Rheine | |
| gezeichnet drawn | Werkstoff Material | Teilnummer Part number | Kz |
| Datum 15.08.11 | DIN | | Lfd.-Nr. Current number |
| Name KU | Gewicht Weight | 913.027 | 542029 |
| | | | Index Change |
| | | | 0 |

Für Montage, Betrieb & Wartung, Betriebs-/ Montageanleitung KTR-N 40310 beachten.
 For assembly, operation & maintenance, observe operating-/ assembly instructions KTR-N 40310.