


Pos.8: O-Ring: 153x6
 Pos.7: Schraube / screw DIN 908: M10x1
 Pos.6: Scheibe / disc DIN 7603: A10x13.5
 Schraubenanzugsmoment (Pos.3) $T_A = 125\text{Nm}$
 screw tightening torque (Pos.3) $T_A = 125\text{Nm}$
 Drehmoment / torque $T_{KN} = 10000\text{ Nm}$
 ACHTUNG / ATTENTION $T_{Kmax.} = 20000\text{ Nm}$
 Schrauben bei Auslieferung handfest angezogen.
 Screws are not tightened at delivery.

Oberflächenguete nach DIN ISO 1302 Reihe 2
 Surface quality acc. to DIN ISO 1302 line 2
 Schutzvermerk ISO 16016 beachten
 Note protection mark acc. to ISO 16016
 Allgmeintoleranzen nach DIN ISO 2768 - mH
 General tolerances acc. to DIN ISO 2768 - mH
 Masstab Scale 3:5
 Format DIN Size A3

GEARex 30 Ø112 Ø112
Bauart FA



	gezeichnet drawn	Werkstoff Material	Teilnummer Part number	Kz	Lfd.-Nr. Current number	Index Change
Datum	30.08.11	DIN		M	543097	0
Name	SCHP	Gewicht Weight	25.200			

Für Montage, Betrieb & Wartung, Betriebs-/ Montageanleitung KTR-N 40310 beachten.
 For assembly, operation & maintenance, observe operating-/ assembly instructions KTR-N 40310.