


Pos.8: O-Ring: 235x8  
 Pos.7: Schraube / screw DIN 908: M10x1  
 Pos.6: Scheibe / disc DIN 7603: A10x13.5  
 Schraubenanzugsmoment (Pos.3)  $T_A = 200\text{Nm}$   
 screw tightening torque (Pos.3)  $T_A = 200\text{Nm}$   
**ACHTUNG / ATTENTION**  
 Schrauben bei Auslieferung handfest angezogen.  
 Screws are not tightened at delivery.

Drehmoment / torque  
 $T_{KN} = 37000\text{ Nm}$   
 $T_{Kmax.} = 74000\text{ Nm}$

|  |                       |  |  |                            |                 |
|--|-----------------------|--|--|----------------------------|-----------------|
| Oberflächenguete nach DIN ISO 1302 Reihe 2<br>Surface quality acc. to DIN ISO 1302 line 2  |                       | Schutzvermerk ISO 16016 beachten<br>Note protection mark acc. to ISO 16016 |  |                            |                 |
| Allgemeintoleranzen nach DIN ISO 2768 - mH<br>General tolerances acc. to DIN ISO 2768 - mH |                       | Masstab<br>Scale   | 2:5  | Format DIN<br>Size         | A3              |
| <b>GEARex 45 Ø172 Ø172</b><br>Bauart FB  |                       |  |  KTR-Kupplungstechnik<br>GmbH<br>D-48407 Rheine |                            |                 |
| gezeichnet<br>drawn  | Werkstoff<br>Material | Teilnummer<br>Part number  | Kz   | Lfd.-Nr.<br>Current number | Index<br>Change |
| Datum<br>30.08.11  | DIN                   |  | M  | 543118                     | 0               |
| Name<br>SCHP   | Gewicht<br>Weight     | 76.978   |  |                            |                 |

Für Montage, Betrieb & Wartung, Betriebs-/ Montageanleitung KTR-N 40310 beachten.  
 For assembly, operation & maintenance, observe operating-/ assembly instructions KTR-N 40310.