



11:50

Für Montage, Betrieb & Wartung, Betriebs-/ Montageanleitung KTR-N 40310 beachten.  
For assembly, operation & maintenance, observe operating-/ assembly instructions KTR-N 40310.

- Pos.8: O-Ring: 108x3.5
- Pos.7: Schraube / screw DIN 908: M10x1
- Pos.6: Scheibe / disc DIN 7603: A10x13.5

Schraubenanzugsmoment (Pos.3)  $T_A = 72\text{Nm}$   
screw tightening torque (Pos.3)  $T_A = 72\text{Nm}$

ACHTUNG / ATTENTION  
Schrauben bei Auslieferung handfest angezogen.  
Screws are not tightened at delivery.

Drehmoment / torque  
 $T_{KN} = 3500\text{ Nm}$   
 $T_{Kmax.} = 7000\text{ Nm}$

Oberflächenguete nach DIN ISO 1302 Reihe 2  
Surface quality acc. to DIN ISO 1302 line 2

Schutzvermerk ISO 16016 beachten  
Note protection mark acc. to ISO 16016

Allgemeintoleranzen nach DIN ISO 2768 - mH  
General tolerances acc. to DIN ISO 2768 - mH

Masstab Scale	4:5	Format DIN Size	A3
------------------	-----	--------------------	----

GEARex 20 Ø31 Ø31  
Bauart FB



KTR-Kupplungstechnik  
GmbH  
D-48407 Rheine

	gezeichnet drawn	Werkstoff Material	Teilnummer Part number	Kz	Lfd.-Nr. Current number	Index Change
Datum	15.08.11	DIN				
Name	STZ	Gewicht Weight	14.233	M	542033	0