


| Permissible misalignments (max. figures may not occur simultaneously) | | | Coupling data | |
|--|--------|--------|---------------------------|---------|
| Angular (each lamina) | Axial | Radial | Nominal torque T_{KN} | 1100 Nm |
| 1.0° | 2.2 mm | 1,5 mm | Maximum torque T_{Kmax} | 2200 Nm |

| | | | | | | |
|--|-----------------------|---------------------------|--|-----|---|-----------------|
| Oberflächenguete nach DIN ISO 1302 Reihe 2 Surface quality acc. to DIN ISO 1302 line 2 | | | Schutzvermerk ISO 16016 beachten Note protection mark acc. to ISO 16016 | | | |
| Allgemeintoleranzen nach DIN ISO 2768 - mH General tolerances acc. to DIN ISO 2768 - mH | | | Masstab Scale | 3:5 | Format DIN Size | A3 |
| RADEX-N 70 E=100 NANA 3 | | | | |  KTR-Kupplungstechnik GmbH D-48407 Rheine | |
| gezeichnet drawn | Werkstoff Material | Teilnummer Part number | | Kz | Lfd.-Nr. Current number | Index Change |
| Datum 07.02.12 | DIN | | | M | 456224 | 1 |
| Name SO | Gewicht Weight | 8.946 | | | | |